



## Chapter 3



**Trailers** 



# Cable Drum, Tubing and Container Trailers BKT 18 up to BKT 80

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



**BKT 18, BKT 23 and BKT 27**

- Easy loading
- High versatility
- Excellent trailing performance



**BKT 60 and BKT 80**

Specifications are subject to change without notice. Output details are depending on use conditions.



**Bagela**

Certified according to DIN EN ISO 9001

# Cable Drum, Tubing and Container Trailers BKT 18 up to BKT 80



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

## Trailing Performance:

The twin-axle chassis absorbs severe shocks and high axle loads, even when crossing rough and bumpy ground.

The trailer runs smoothly and does not jump. The extreme loads generated by starting and braking are damped down and thus transmitted only partly to the hook of the towing vehicle.

The type BKT 18, BKT 23 and BKT 27 are hot-dip galvanised serially. The type BKT 40, BKT 60 and BKT 80 are primed and finished in RAL 3020. We recommend the hot-dip galvanisation too.

## Versatility:

Trailers of the series BKT 18 up to BKT 27 are applicable for transporting HDPE-tubing drums, cable drums, Pipe coil cages, Loading platforms and carrier set for up to 9 micro pipe drums. All Bagela trailers of series BKT could be used as container transporter up to 9 m<sup>3</sup> without conversion work.

## Easy Loading:

Irrespective of ground conditions one man can load the trailer in a couple of minutes. The trailer shifts the cable drum into pick up position by fingertip control and hauls it to trailing position between the axles.

### Technical Data

Type height adjustable	BKT 18 100	BKT 23 100	BKT 27 100	BKT 40 10	BKT 60 100	BKT 80 100
Length (mm)	4950-5200	4950-5200	4950-5200	4200	5050-5400	5050-5400
Width (mm)	2550	2550	2550	2550	2550	2550
Height (mm)	1900-2550	1900-2550	1900-2550	2260	2450	2450
Empty weight (kg)	750	820	860	1500	2100	2500
Payload (kg)	1750	2180	2640	4100	6100	8500
Total weight (kg)	2500	3000	3500	5600	8500	11000
Brake	overrun	overrun	overrun	air pressure	air pressure	air pressure
Max. drum-Ø (mm)	2800	2800	2800	3000	3000	3000
Max. tube coil-Ø (mm)	3700	3700	3700	-	-	-
Clear loading width (mm)	1720	1720	1720	1720	1720	1720
Tyre size	195/70R14	195/70R14	195 R14C	8.25 R15	245 70R 17,5	245 70R 17,5
Tow bar height adjustable (mm)	400-1100	400-1100	400-1100	820-930	780-1050	780-1050
Order-No.	008.023.00	008.001.00	008.002.00	008.009.00	008.003.10	028.530.10
Type fixed draw gear	BKT 18 100	BKT 23 100	BKT 27 100			
Length (mm)	4000	4000	4000			
Empty weight (kg)	710	770	820			
Payload (kg)	1790	2230	2680			
Order-No.	008.023.10	008.001.10	008.002.10			

Specifications are subject to change without notice. Output details are depending on use conditions.



# Cable Drum, Tubing and Container Trailers BKT 18 up to BKT 80

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



**BKT 40**



**BKT 23/27 with HDPE-tubing drum**



## **For BKT 18 up to BKT 80**

- Hydraulic Power Pack for drum lifting and driving with petrol engine and lockable steel sheet protection hood
- Drum drive without Hydraulic Power Pack
- Aluminum shaft for cable drums with lathed bearing points and with sliding bearings



## **For BKT 18 up to BKT 27**

- Uncoiling cage for special length 290 m, pipe dia.: 160 mm

Specifications are subject to change without notice. Output details are depending on use conditions.



**Bagela**

Certified according to DIN EN ISO 9001



# Cable Drum, Tubing and Container Trailers BKT 18 up to BKT 80



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

## For BKT 18 up to BKT 27

- Additional acceptance for micro duct drums



Tipping container	2,3 m <sup>3</sup>	<b>BKT 18 - 27</b>
Tipping container	4,0 m <sup>3</sup>	<b>BKT 40</b>
Tipping container	4,5 m <sup>3</sup>	<b>BKT 18-27 / 60 / 80</b>
Tipping container	4,5 m <sup>3</sup>	<b>BKT 18 - 27 / 60 / 80</b>
Tipping container	9,0 m <sup>3</sup>	<b>BKT 60 / 80</b>

Acceptance arbor for container



## Mechanical drum brake BKT 10 - BKT 27

Galvanized, steel shaft with plain bearings instead of unsupported shaft and clamps.



Specifications are subject to change without notice. Output details are depending on use conditions.



# Cable Drum, Tubing and Container Trailers BKT 10 up to BKT 15

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories

## Type BKT 10 - 12 - 15

The BKT 10-15 gets loaded by a tilting frame which is operated by a manually operated hydraulic pump and two double acting hydraulic cylinders.



## Type BKT 10K - 12K - 15K

The loading frame is tilted up with a non-recoiling, hand-operated windlass and secured by two eccentric claps.

Upon request, all trailers may be delivered with extendible loading jibs for picking up tube reels (for BKT 10 and BKT 12/15 serially).

Larger diameters of pipe coils than mentioned for the cable drums can be transported with that additional extensions.

**The trailers of both construction series are hot galvanised.**



BKT 10 K with tube reel RH 63

### Technical Data

Type height adjustable	BKT 10	BKT 12	BKT 15	BKT 12/15	BKT 10K	BKT12K	BKT 15K
Length (mm)	4330	4540	4600	-	4030	4290	4350
Width (mm)	2140	2340	2340	2340	2140	2340	2300
Height (mm)	1750	1980	2000	2100	1750	1980	2000
Payload (kg)	970	1080	1500	-	950	1200	1500
Total weight (kg)	1350	1600	2300	1600	1350	1650	2300
Max. drum/tube coil Ø (mm)	2600	2500	2500	2800/3800	2600	2500	2500
Clear loading width (mm)	1360	1580	1580	1580	1360	1580	1580
Order-No.	008.020.01	008.021.01	008.022.01	-	008.015.01	008.016.01	008.017.01
<b>Type fixed draw gear</b>							
Length (mm)	3320	3780	3740	3930	3220	3780	3740
Payload (kg)	970	1100	1500	1080	950	1200	1500
Order-No.	008.020.00	008.021.00	008.022.00	008.740.00	008.015.00	008.016.00	008.017.00

Specifications are subject to change without notice. Output details are depending on use conditions.



**Bagela**

Certified according to DIN EN ISO 9001

# Cable Drum, Tubing and Container Trailers BKT 10 up to BKT 15



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

## Cable drum trailer type BKT 15

The tilting frame tilts hydraulically backwards and the platform swings behind the trailer.



## Cable drum trailer type BKT 15 with a 4 kW hydraulic power pack and a single arm drum drive

especially for fibre optic cables; The hydraulic power pack is available for all types of the hydraulic series BKT 10 - BKT 15.



## Cable drum trailer type BKT 12/15 with extendible pick-up jibs and tube coil cage RH 160

The pick-up jibs and the cage may be adjusted to coil diameters of up to 3700 mm. After the packing straps have been removed from the coil, the tube can be uncoiled out of the centre.

### Capacity:

Tube-Ø: 90-160 mm

Max. length: 100 m



Specifications are subject to change without notice. Output details are depending on use conditions.





# Cable Rewinding Unit KSP 80

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



The KSP 80 pulls cable rests from a submarine cable ship and rewinds it directly on cable drums of up to 80,000 kg total weight. The drums get tensed up by the drive rollers. A tensile and braking force of up to 110 kN depending on the drum diameter.

The winding and rewinding speed is regulated steplessly between 0 up to 25 m/min. What means that cables can be rewinded even in steep trails.

## Application fields:

- Laying of submarine cables
- Connection of wind parks
- Cable laying in steep trails



Specifications are subject to change without notice. Output details are depending on use conditions.



## Bagela

Certified according to DIN EN ISO 9001



# Cable Rewinding Unit KSP 80



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

## Layered Arrangement:

A remote control with potentiometer controls the drive rollers and the layered arrangement.

## Control of the Cable Rewinding Unit:

The remote control regulates speed and direction of the drum and the layered arrangement. Therefore the operator is out of the danger zone and at the same time flexible to supervise the rewinding.

## External Hydraulic Aggregate BHA 22060:


For powering the cable rewinding unit an external hydraulic aggregate is to be used.

The BHA 22060 is sound insulated and to be positioned in sufficient distance.

Design flow rate: 60 l/min  
Design pressure: 220 bar  
Max. pressure: 250 bar

## Hydraulic Control:

The gauges indicate the locking and drum drive pressure. They inform permanently about the current pressures and how much reserves are remaining. Especially for the winding these information are crucial.



Type	Load kg	Weight kg	Drum -Ø mm	Max.Drum Width mm	Length mm	Width mm	Height mm	Order-No.
<b>KSP 80</b>	80000	8600	2500 - 5000	6000	9000	3572	2000	<b>029.400.00</b>
<b>Layered A.</b>	-	2000			9524	2124	3000	<b>029.430.00</b>
<b>BHA 22060</b>	-	990			1520	920	1620	<b>010.170.00</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



# Cable Drum Transport and Laying Trailer BTT 300

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



## BTT 300.10V hydraulic extendable

Cable trailers of this construction series are capable of picking up, transporting and unreeling heavy power cable drums from 2200 up to 4500 mm diameter and 30 t weight. For drums of dia. 2200 - 3270 mm are additional lifting pockets available. For larger drum diameters this type of trailer offers a solution too.

The rear open U-type design of the trailer, allows the cable drum to be placed directly into loading position, where it is only lifted up for transport or payout by two vertical rows of lifting pockets driven by a power-hydraulic system.

This trailer gets loaded by the motor hydraulic lift. The air suspension enables the laterally lowering of the trailer to adapt to angular standing drums on difficult ground. This suspension assures the permanent load spreading on all tires while driving.

### Optional accessories:

- Twin roller drum drive with hydraulic press cylinders
- Additional pockets for picking up small cable drums
- Hydraulic extendable system
- Remote control

Specifications are subject to change without notice. Output details are depending on use conditions.



## Bagela

Certified according to DIN EN ISO 9001

# Cable Drum Transport and Laying Trailer BTT 300



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

## Standard version:

In the standard version the BTT 300.10E is flanged and the speed is limited to 10 km/h.

For shipment the trailer can be separated in 3 parts.

## Remote Control:

The remote control with 10 m cable ensures an optimal overview to the operator while loading, reeling and unreeling (fast- slow)

For hydraulic extendable versions on request.



## Extendable Version:

For driving on public roads or for shipment the trailer is retractable to an outer width of 2550 mm. Admitted speed is 80 km/h (depending on national road restrictions).



## Technical Data

Type	Payload kg	Total weight kg	Max. Drum dia. mm	Max. Loading width mm	Chassis		Length mm	Width mm	Height mm	Order-No.
					Type	Brake				
<b>BTT 300.10E</b>	32060	39760	5000	1690	7000	Air press.	8750	2550	3750	<b>048.500.00</b>
<b>BTT 300.10V</b>	30000	39760	5000	3200	7000	Air press.	8750	2550-4060	3750	<b>048.501.00</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



# Cable Drum Transport and Laying Trailer BTT 131.80 hydraulic extendable

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



## **BTT 131.80V hydraulic extendable with power hydraulic drum drive and lifting system**

The connection of the expanding renewal energy e.g. offshore wind parks demands a massive net extension. Instead of overhead lines, high-voltage cables with large conductor cross-sections are laid in the ground. In order to avoid cable joint boxes the cable manufacturers produce the greatest possible lengths and supply the cable only on broad drums what means the laying with conventional trailers could not be managed.

Cable Drum Transport and Laying Trailer BTT 131.80V could be extended hydraulically. The air suspension enables the laterally lowering of the trailer to adapt to angular standing drums on difficult ground.

The U-type design of the trailer, open at the rear, enables the mounting of a different triangle towing bar in which the hydraulic cylinders for the widening function are implemented.

- **Simple extending operation of the trailer and the drum drive via the own hydraulic system**
- **Just secure in the required width with the locking bolts, ready**
- **The drum axles in the suitable length are fixed at the trailer**

Specifications are subject to change without notice. Output details are depending on use conditions.



## **Bagela**

Certified according to DIN EN ISO 9001



# Cable Drum Transport and Laying Trailer BTT 131.80 hydraulic extendable



Cable Laying Machines

Pipe Renewal Winches


Asphalt Recycler

Accessories

## BTT 131.80V narrowest way

Extending:

The total width of the retracted trailers is 2550 mm, so you need no special permit for a MOT approval. A maximum widening up to 4000 mm can be reached at the building site. The maximum loading width could be extended from 1690mm up to 3090 mm (the dimensions are depending on the trailer type). The drum drive is divided and will proceed the extending automatically.



## BTT 131.80V extended



Operation:

The operation instruments for loading and controlling the drum drive are located at the left rear side. The operation lever for extending at the left front. While this function the trailer must be moved.

**We build all hydraulic extendable trailers in fixed version which is flanged too!**



### Technical Data

Type	Payload kg	Total weight kg	Max. Drum dia. mm	Loading width mm	Chassis		Length mm	Width mm	Height mm	Max. km/h	Order-No.
					Type	Brake					
<b>BTT 131.80V</b>	11700	18000	4500	1690-3090	700	Air press.	7950	2550-3950	3295	80	<b>048.400.00</b>
<b>BTT 131.80</b>	13000	18000	4500	1690	700	Air press.	6000	2550	3295	80	<b>048.801.00</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



# Cable Drum Transport and Laying Trailer

## BTT 100.80 BTT 160.25 BTT 200.20

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



### BTT 200.20 with drum drive in flanged version

Cable trailers of this construction series are capable of picking up, transporting and unreeling heavy power cable drums of up to 16 t weight.

The U-type design of the trailer, open at the rear, allows the cable drum to be placed directly into loading position, where it is only lifted up for transport or payout by two vertical rows of lifting pockets. In the standard version of the trailer the drum is lifted by hand-operated pump via two separately controllable hydraulic jacks.

#### Optional accessories:

- Power hydraulic lifting system
- Power hydraulic lifting system and drum drive
- Additional pockets for picking up small cable drums
- Bigger drum dia. on request

#### Technical Data

Type	Payload kg	Total Weight kg	Max. Drum dia. mm	Loading Width mm	Chassis		Length mm	Width mm	Height mm	Max. km/h	Order-No.
					Type	Brake					
<b>BTT 100.80</b>	10000	13000	3600	1720	700	Air press.	6000	2550	2600	80	<b>028.603.00</b>
<b>BTT 160.25</b>	16000	19100	3600	1660	700	Air press.	6000	2550	2600	25	<b>028.605.00</b>
<b>BTT 200.20</b>	19500	24000	3600	1697	700	Druckl.	6500	2750	2775	20	<b>028.607.00</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



## Bagela

Certified according to DIN EN ISO 9001

# Cable Drum Transport and Laying Trailer

## BTT 5825 BTT 7525 BTT 8020E BTT 140.20E



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

### BTT 5825 / 7525

The U-shaped structure of the trailer with its open rear allows the backing up directly to the position of the cable drum into the BTT 5825/7525. After the drum shaft has been pushed through the centre bore of the drum and engaged into the appropriate carrying pockets of the trailer, the drum is lifted hydraulically and ready for transport and unreeling. With the standard version, the drum is lifted by hydraulic hand pump via two individually controllable cylinders. The BTT 5825M and BTT 7525M differ in the loading with a hand-operated windlass.

#### Optional extras:

- Power hydraulic system for lifting and rotating the drum
- Additional carrying pockets for smaller drums

### BTT 8020 E / BTT 140.20 (E= Export version)

The trailer Type BTT 8020 E/ BTT 140.20 is based on the Type BTT 7525 and differs only in the equipment. Here it is reduced to a minimum to keep the price low. It is build without light and brake system and mud guards but with parking brake.

#### Optional extras:

- Power hydraulic system for lifting and rotating the drum
- Additional carrying pockets for smaller drums

All trailers of the BTT series are available as a collapsible version, which reduces loading space and freight charges.



BTT 5825 / 7525 with extras  
(picture without mud guards and lightning system)



### Technical Data

Type	Payload kg	Total Weight kg	Max. Drum dia. mm	Loading Width mm	Chassis		Length mm	Width mm	Height mm	Max. km/h	Order-No.
					Type	Brake					
<b>BTT 5825</b>	5800	6950	3200	1685	-o	Air Press..	4000	2550	2300	25	<b>028.600.00</b>
<b>BTT 5825 M</b>	5800	6950	3200	1685	-o	Air Press	4000	2550	2300	25	<b>028.600.50</b>
<b>BTT 7525</b>	7500	8650	3200	1685	-o	Air Press	4000	2550	2300	25	<b>028.601.01</b>
<b>BTT 7525 M</b>	7500	8650	3200	1685	-o	Air Press	4000	2550	2300	25	<b>028.601.51</b>
<b>BTT8020 E</b>	8000	9150	3200	1685	-o	Parking brake	4000	2550	2300	20	<b>028.601.30</b>
<b>BTT 140.20E</b>	14000	16200	3600	2389	-o	Parking brake	4625	3582	2600	20	<b>028.786.00</b>

Specifications are subject to change without notice. Output details are depending on use conditions.





# Compact Pipe Reel Trailer BRT 65 for „Compact Pipe“

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



For winding and transportation of compact inline pipe of 400 mm dia., reels of an outer diameter of 3700 mm are needed. For carrying such large reels we have designed our trailer BRT 65 with an open rear side to enable the reel to be placed inside the trailer frame for being picked up. Serially the trailer is equipped with a rear gate to be opened to one side.



Two vertical pocket jacks, which may independently be moved up and down by an engine-driven hydraulic drive system and which are secured for transport by locking pins, lift the reel.

The twin roller reel drive system for turning and braking the reel is also driven by this hydraulic drive system.

The towing eye is height adjustable between 840 up to 950 mm.

Specifications are subject to change without notice. Output details are depending on use conditions.



## Bagela

Certified according to DIN EN ISO 9001



### Hydraulic drum drive and brake

The twin driving rollers, each running on three bearings, have a diameter of 150 mm and thus provide high frictional power. Each roller consists of several segments.

#### Advantage:

Since the rollers are worn locally, i.e. where they get into contact with the reel flanges, there is no need of replacing both rollers at the same time; instead the segments may be interchanged among one another.



### Mechanical drum brake

In order to resist the high expansion power of the „Compact Pipe“ coil, the twin driving rollers are equipped with a mechanical disc brake.



### Central control board at the rear and hydraulic rear supports

#### Advantage:

All controls are provided at a central position at the rear for easy reel handling, i.e. loading, unloading, reeling and unreeling.



### Supported Rollers at the front and back

These rollers protect the Compact-Liner from damages. Loose loops of the liner were guided over the rollers to protect the liner from sagging.



### Technical Data

Type	Payload-	Empty-	Total	Max.	Max.	Chassis		Length	Width	Height	Order-
						Type	Brake				
BRT 65	6500 kg	2420 kg	8920 kg	3700 mm	1630 mm	70	Air press	6500	2550	2500	008.513.00

Specifications are subject to change without notice. Output details are depending on use conditions.



# Tube Drum Transport Trailers

## BRT 25 up to BRT 50

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



**BRT 25 picking -up a U-liner drum**



It is essential that contractors should adapt their tools and equipment to the development of underground tube renewal techniques. While tube manufacturers first and foremost think of the most efficient way of manufacturing and packing, tube laying contractors are faced with the problem of how to transport and install the tubing.

To be able to transport a drum of U-liner with a width of 2150 mm and a diameter of 3200 mm, a completely new loading concept had to be developed. On the basis of the BKT series of cable trailers a loading frame has been designed which lifts the tube drum from the rear of the trailer by engine/hydraulic drive over the rear axle and lowers it on the centre of the loading platform exactly between both axles.

Almost the full width of the trailer is used as loading area without exceeding the permissible width according to the motor vehicles licensing regulations.

Specifications are subject to change without notice. Output details are depending on use conditions.



# Bagela

Certified according to DIN EN ISO 9001

# Tube Drum Transport Trailers

## BRT 25 up to BRT 50



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

### BRT 50 With Drum-Drive



#### Drum drive system with brake device:

This accessory prevents expanding the coils from passing over the sides of the drum. Moreover, a rubber friction roller is provided for braking and driving the drum as required.

When the U-liner is lowered into the pit, the drive system remains operational and the rubber friction roller remains pressed against the drum.

#### Technical Data

Type	Payload	Total weight	Max. Drum dia.	Max. Drum width	Chassis		Length	Width	Height	Order-No.
	kg	kg	mm	mm	Type	Brake	mm	mm	mm	
<b>BRT 25</b>	2500	3500	3000	2150	100	Overrun	4400	2500	2500	<b>008.005.00</b>
<b>BRT 42</b>	4400	6570	3000	2150	100	Air press.	5100	2500	2600	<b>008.006.00</b>
<b>BRT 50</b>	5800	8800	3200/3400/3600	2315	100	Air press.	5900	2550	2750	<b>028.340.00</b>

Specifications are subject to change without notice. Output details are depending on use conditions.





# Tube coil haulage and uncoiling trailer BRVT 09 und BRVT 16

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



There are a lot of reasons for a small light tube coil trailer:

- 80 % of all standard tube coils have a winding length of 100 m.
- With a pay load of 900 kg and a permissible total weight of 1600 kg the BRVT 09 is to be classified as a passenger car trailer. The large trailers for 300 m pipe lengths have a permissible total weight of 3000 kg and require a small truck or a passenger car with tachograph as towing vehicle.
- The BRVT 09 is a good opportunity to the larger and more expensive coil transport trailer



Whether with HDD drilling machines or all in pipe renewal processes, especially on urban working sites, the space is confined.

With BRVT 09/BRVT 16 the pipe is guided from the top out of the basket parallel to the coil under the axle of the trailer to the rear.

There is no bending tension on the pipe coil. The roll resistance is less than of conventional solutions. No more inner rollers are necessary and the inner end of the pipe can be pulled into the coil.  
The BRVT 16 is able to load and uncoil wider pipe coils.

## Technical Data

Type	Pay load kg	Empty weight kg	Max. dia. Pipe Max. dia. Pipe coil mm	Max. Coil Width mm	Length mm	Width mm	Height mm	Order-No.
<b>BRVT 09</b>	680	920	3750 / 160	1100	5070	2250	2950	<b>038.700.04</b>
<b>BRVT 16</b>	1400	1100	3750 / 160	1500	5150	2300	3030	<b>038.700.06</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



## Bagela

Certified according to DIN EN ISO 9001



# Tube Coil haulage and uncoiling trailers

## BRVT 17 / Uncoiling cage



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

- Lateral movable limit bar for limitation of different pipe coil width.
- The quick roller change system shortens the changeover time for 60 % and lowers the danger of accidents which is imminent by two handed screwing.
- Depending on the big loading width coil dimensions of up to 180 mm can be loaded.
- The sturdy lower rollers enable the transport of HDPE-tubing drums too.
- Simultaneous uncoiling of three pipe coils is possible (pipe dia. 100 mm, pipe coil length: 100 m)



**Attention: The inner end of the pipe is to be cut. It has to be flush to the pipe coil!**

Uncoiling cages can be used also without trailer as freestanding device. Tool trailer are suitable likewise, however a safe attachment must be ensured.

The Bagela cable drum trailer of the series BKT 23 and 27 is equipped with the necessary attachment for the Uncoiling cage and are able to load and unload it independently.

In addition, the Uncoiling can be used in a cable drum trailer of strange brand.



### Technical Data

Type	Pay load	Empty weight	Total weight	Max. dia. pipe coil	Loading width	Chassis Type	Brake	Length mm	Width mm	Height mm	Order-No.
<b>BRVT 17</b>	1700 kg	1300 kg	3000 kg	3700 mm	1720 mm	700	overrun	5800	2520	3050	<b>038.700.00</b>
<b>BRVT 17</b>	1800 kg	1200 kg	3000 kg	3700 mm	1720 mm	700	overrun	5300	2520	3050	<b>038.700.10</b>
<b>Cage</b>		450 kg		3700 mm	1465 mm			3900	1994	2570	<b>008.339.01</b>
<b>Cage wide</b>		580 kg		3700 mm	1700 mm			3900	2230	2570	<b>008.339.02</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



# Tube Coil Pick-up and Pay-out Trailer BRT 20

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories



The BRT 20 is able to pick up, load and uncoil pipe coils without any help. Even laying coils can be picked up without any auxiliary equipment. Tube coils of varying diameters may be picked up with the aid of the vertical hydraulic jacks and put down on the bearing rollers. Then three guiding rollers are inserted on the inside of the coil, and the coil is ready for unreeling.

Since the coils are picked up from the rear, all hydraulic control levers are arranged at the rear. The operator's stand within the slewing range of the pick-up frame is provided with a protection guard.



Even coils lying flat on the ground can be picked up by the frame and slewed into the roller cage. The pick-up shaft runs on bearings and is provided with spherical ends, which prevent the shaft from being stressed irrespective of the relative position of the lifting arms. During tube unreeling two steadying wheels hold the narrow coils (100m length) in centre position.

**Attention:** The inner end of the pipe has to be cut flush to the pipe coil!

## Technical Data

Type	Pay-load kg	Total- Weight kg	Max. dia. reel coil mm	Loading Width mm	Chassis		Length mm	Width mm	Height mm	Order-No.
					Type	Brake				
BRT 20	1600	3500	3700	1500	Too	Auflauf	5850	2500	3050	038.250.00

Specifications are subject to change without notice. Output details are depending on use conditions.



**Bagela**

Certified according to DIN EN ISO 9001

# Tube Coil Reels RBH 40 and RBH 63



Cable Laying Machines

Pipe Renewal Winches

Asphalt Recycler

Accessories

Gas or water pipes made of PE up to a diameter of 63 mm are generally delivered in bundles. When the packing straps are removed the coils will expand and find to be muddled up due to their own tension.

## Tube laying until now, WITHOUT Bagela Coil Reels:

- High labour costs while tube laying
- Danger of scratches on the tube
- Chaos at site due to expanding of the remaining coil



## Tube laying today, WITH Bagela Coil Reels:

- Cost-saving tube laying by one person only
- Easy and careful handling of the tubes
- Bundling of the remaining tube into the reel
- Easy storing and re-usage of the remaining tube



The Coil Reels type RH 40 and RH 63 may be used in a cable drum trailer, without the rack.



**Bagela  
Coil Reel  
with standing rack**

### Technical Data

	Pipe	Tube coil		Max. Coil dimensions	Length	Width	Height	Weight	Order-No.
Type	Ø mm	outer-Ø mm	Width mm	Length (m) / Ø (mm)	mm	mm	mm	kg	
<b>RBH 40</b>	max. 40	max. 1350	max. 400	200 / 32 100 / 40	1450	730	1500	95	<b>004.450.00</b>
<b>RBH 63</b>	max. 63	max. 2200	max. 570	400 / 50 300 / 63	2350	1060	2470	215	<b>004.750.02</b>

Specifications are subject to change without notice. Output details are depending on use conditions.



# Notes

Cable Laying Machinery

Pipe Renewal Winches

Asphalt Recycler

Accessories

Grid area for notes.



**Bagela**

Certified according to DIN EN ISO 9001